


— S —
HURAGAN 3




 red-silver-graphite

 700C

 alu 6061X-lite

 47/50/53/56 cm

 18 speed

 9,6 kg

HURAGAN 3

Technical data

WHEEL SIZE / FRAME	700C / alu 6061 X-lite	RIMS	Ryde DP16
SIZE	47cm / 50cm / 53cm / 56cm	FRONT HUB	aluminium
FORK	Full Carbon Tapered	REAR HUB	aluminium
DAMPER	—	CASSETTE	Shimano CS-HG400 11-28T 9 speed
DRIVETRAIN	2×9	HANDLEBAR	Romet aluminium 420mm
FRONT SHIFTERS	Shimano Sora ST-R3000 2 speed	STEM	Romet aluminium 90/100/110mm
REAR SHIFTERS	Shimano Sora ST-R3000 9 speed	SEAT POST	Romet aluminium 27,2 mm 300/350/400mm
FRONT DERAILLEUR	Shimano Sora FD-3000	GRIPS	—
REAR DERAILLEUR	Shimano Sora RD-R3000	SADDLE	Vader
CRANKSET	Shimano Sora FC-R3000 50/34T 165/170mm	PEDALS	FP-971 aluminium
FRONT BRAKE	Shimano Sora BR-R3000	FRONT LAMP	—
REAR BRAKE	Shimano Sora BR-R3000	REAR LAMP	—
FRONT BRAKE DISC	—	WEIGHT	9,6 kg
REAR BRAKE DISC	—	COLOURS	red-silver-graphite
TYRES	Michelin Lithion 3 700×25C		

Geometry

	S	M	L	XL
Tyre size	28"	28"	28"	28"
A - frame size	470 mm	500 mm	530 mm	560 mm
B - top tube length	521 mm	550 mm	570 mm	590 mm
C - chainstay length	410 mm	410 mm	410 mm	410 mm
D - seat tube angle	73°	73°	73°	73°
E - head tube angle	61°	60°	60°	61°
F - wheel base	996 mm	990 mm	1006 mm	1020 mm
G - head tube length	130 mm	150 mm	170 mm	190 mm
H - fork length	367 mm	367 mm	367 mm	367 mm
Stack	520 mm	543 mm	562 mm	584 mm
Reach	388 mm	389 mm	403 mm	411 mm
Standover height	—	—	—	—
Maximum tyre size	700×25C	700×25C	700×25C	700×25c

