



E-MUSTANG 2.0

725Wh / 540Wh



 graphite
-silver



Shimano EP6



250W 85Nm



725Wh / 540Wh



10 speed

E-MUSTANG 2.0 725Wh / 540Wh**Technical data**

MOTOR / PERFORMANCE	Shimano EP6 mid-mount, 250 Watt , 85Nm torque sensor	TYRES	Veetire Crown Gem 29"×2,30"
CONTROL UNIT	display Shimano SC-EN500	RIMS	aluminium doublewall RMT Components
BATTERY	725Wh / 540Wh	FRONT HUB	aluminium 15mm/110mm
CHARGER	4,5A	REAR HUB	aluminium 12mm/148mm
WHEEL SIZE / FRAME	29" / alu 6061	CASSETTE	Shimano Cues CS-LG300-10, 11-48T , 10 speed
SIZE	M – 18" / L – 20"	HANDLEBAR	RMT Components aluminium 720mm , 31,8mm
FORK	Suntour X1- BoostAIR-LOR, 120mm , tapered	STEM	Satori New Viper 80mm Int. cable routing, 31,8mm
DAMPER	—	SEAT POST	RMT Components aluminium 30,9mm/350mm
DRIVETRAIN	1×10	GRIPS	Wittkop Medicus Sport
FRONT SHIFTERS	—	SADDLE	Selle Royal Vivo Ergo Sport
REAR SHIFTERS	Shimano Cues SL-U6000 10 speed	PEDALS	FP-868ZU
FRONT DERAILLEUR	—	FRONT LAMP	—
REAR DERAILLEUR	Shimano Cues RD-U6000	REAR LAMP	—
CRANKSET	Shimano SM-CRE80-B 34T 170mm	WEIGHT	—
FRONT BRAKE	Shimano BL-MT200 hydraulic	COLOURS	graphite-silver
REAR BRAKE	Shimano BL-MT200 hydraulic		
FRONT BRAKE DISC	180mm		
REAR BRAKE DISC	160mm		

Geometry

	M	L
Tyre size	29"	29"
A - frame size	457 mm	508 mm
B - top tube length	608 mm	649 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	73,1°	73,1°
E - head tube angle	69°	69°
F - wheel base	1158 mm	1200 mm
G - head tube length	130 mm	140 mm
H - fork length	530 mm	530 mm
Stack	663 mm	673 mm
Reach	411 mm	449 mm
Standover height	821 mm	858 mm
Maximum tyre size	2.60"	2.60"

