>>> GRAVEL SPEEDERO











MADE FOR SPEED. IT DOESN'T MATTER IF YOU RIDE ON ASPHALT, COBBLES, FOREST PATHS, SAND, GRASS OR GRAVEL. TUBELESS READY. HOOKLESS COMPATIBLE.

The tubeless ready Speedero always provides uncompromising acceleration and ease of riding with plenty of grip and cornering safety. The wide tread and the durable flexible Jubena layer covering the sidewalls, protect the tyre from receiving damage from stones. A Puncture proof ply under the tread minimizes the risk of punctures and contributes to the overall reliability of the tyre. The high TPI casing construction, together with the soft tread compound, smoothes out any surface and prevents the tyre from bouncing on uneven surfaces. The Speedero is also made to be long lasting and guarantees high mileage.

TUBELESS READY TYRES	SIZE	WEIGHT	PRESSURE	TPI Count Sidewall area / Under the tread
GRAVEL SPEEDERO	36-622 (700x36C)	390 g	2-5 bar (30-70 p.s.i.)	210/375
GRAVEL SPEEDERO	40-622 (700x40C)	430 g	2-5 bar (30-70 p.s.i.)	210/375
GRAVEL SPEEDERO	44-622 (700x44C)	450 g	1.7-4 bar (24.7-58 p.s.i.)	210/375

>>> GRAVEL SPEEDERO HD







MADE FOR SPEED. IT DOESN'T MATTER IF YOU RIDE ON ASPHALT, COBBLES, FOREST PATHS, SAND, GRASS OR GRAVEL. TUBELESS READY, HOOKLESS COMPATIBLE.

The tubeless ready Speedero always provides uncompromising acceleration and ease of riding with plenty of grip and cornering safety. The wide tread and the durable flexible Jubena layer covering the sidewalls, protect the tyre from receiving damage from stones. A Puncture proof ply under the tread minimizes the risk of punctures and contributes to the overall reliability of the tyre. The Speedero is also made to be long lasting and guarantees high mileage.

This HD version extends the existing gravel range with focus on higher loads and operating pressures. Modified construction with stronger warp threads achieves higher durability with only a 30 grams weight increase.

	TUBELESS READY TYRES	SIZE	WEIGHT	PRESSURE	TPI Count Sidewall area / Under the tread
V	GRAVEL SPEEDERO HD	40-622 (700x40C)	460 g	2-5 bar (30-70 p.s.i.)	130/255